



# ENGINE FLUSH

**PN: R1201**

**TECHNICAL DATA SHEET**

## 1. PRODUCT IDENTIFIER

Engine Flush

**1.1 Relevant uses:** removes operational contamination and resin deposits in the entire oil and lubricating circuit, residue and carbonization in the piston rings and the upper cylinder area, neutralizes harmful engine acids. This leads to improved engine performance. In addition, Engine Flush protects the engine during the cleaning process through highly effective lubrication components. Used for all petrol & diesel-powered engines

**1.2 Details of the supplier of the safety data sheet**  
 Company: RHINOMOTIVE LTD - UK 71-75 SHELTON STREET, LONDON, UNITED KINGDOM  
 Emergency Contact Number: +971 4 329 7775  
 Email: info@rhinomotive.com

## 2. AVAILABLE SIZES

375ml

## 3. TECHNICAL SPECIFICATIONS

No	Description	Units
1	Physical state	Liquid
2	Colour	Green
3	Odour	Aromatic
4	Initial boiling point & boiling range:	180 - 220 °C
5	Flashpoint	65 °C
6	Ignition temperature	> 200 °C
7	Vapour pressure at 68 °F	20 Hpa
8	Density at 68 °F	0,790 - 0,820 G/Cm <sup>3</sup>
9	Volume	375ml

## 4. PRODUCT CONSTRUCTION

CAS No	Chemical name	Percentage	
	EC No	Index No	REACH No
	Classification according to Regulation (EC) No. 1272/2008 [CLP]		
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics	80 - < 100 %	



# ENGINE FLUSH

**PN: R1201**

	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
85535-85-9	Chlorparaffines C14-C28			1 - < 5 %
	287-477-0		01-2119519269-33	
	Lact., Aquatic Acute 1, Aquatic Chronic 1; H362 H400 H410 EUH066			

## 5. DIRECTIONS FOR USE

- Add to old oil, run engine at idle for 10-15 minutes
- Drain as normal
- Fit new filter and fill with new oil
- Treats up to 6 liters of oil
- Recommended to add RHINOMOTIVE Oil Booster R1222 for optimum engine output and protection
- Suitable for all petrol & diesel-powered engines

## 6. CONSUMPTION

375ml treats up to 6 liters of oil

## 7. REACTION TIME

Approx. 15 minutes with engine running

## 8. SHELF LIFE

24 months

## 9. PERFORMANCE PROPERTIES

Not Applicable

## 10. STORAGE

- Store in a dry and well-ventilated area between 20 - 30°C and 30 - 60% relative humidity

## 11. TEST REPORT

Not Applicable



# ENGINE FLUSH

**PN: R1201**

## 12. DISCLAIMER

TECHNICAL DATA SHEET

Important Notice Purchaser: RHINOMOTIVE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The user is responsible for determining whether the RHINOMOTIVE product is fit for a particular purpose and suitable for user's application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform among the many factors that can affect the use and performance of a RHINOMOTIVE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the RHINOMOTIVE Automotive product to determine whether it is for a particular purpose and suitable for user's methods of application.

Limitation of Remedies and Liability: if the RHINOMOTIVE product is proved to be defective. THE EXCLUSIVE REMEDY, AT RHINOMOTIVE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE RHINOMOTIVE PRODUCT. RHINOMOTIVE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

**PRO  
SERIES** | **USE IT AND SEE  
THE DIFFERENCE**

