

# CERAMIC EXTREME+ ABRASIVE SHEETS P400

**PN: R1526**

## 1. PRODUCT IDENTIFIER

Ceramic Extreme+ Sheets P400

**1.1 Relevant uses:** for sanding many different substrates, used for a variety of jobs including paint removal and feather edging and removal features an updated coating that levels surface defects on clear coat and greatly reduces pigtails. Aluminum oxide abrasive cuts fast, lasts a long time, resists loading with or without hole pattern designs and leaves a consistent smooth finish.

**1.2 Details of the supplier of the safety data sheet**

Company: RHINOMOTIVE LTD - UK 71-75 SHELTON STREET, LONDON, UNITED KINGDOM

Emergency Contact Number: +971 4 329 7775

Email: [info@rhinomotive.com](mailto:info@rhinomotive.com)

## 2. AVAILABLE SIZES

No.	P.N.	Product name	Grit	Size	Length	Quantity
1	R1521	Ceramic Extreme+ Abrasive Sheets P80	P80	70mmx198mm	11m	55 Sheets/Box
2	R1522	Ceramic Extreme+ Abrasive Sheets P120	P120	70mmx198mm	11m	55 Sheets/Box
3	R1523	Ceramic Extreme+ Abrasive Sheets P180	P180	70mmx198mm	11m	55 Sheets/Box
4	R1524	Ceramic Extreme+ Abrasive Sheets P240	P240	70mmx198mm	11m	55 Sheets/Box
5	R1525	Ceramic Extreme+ Abrasive Sheets P320	P320	70mmx198mm	11m	55 Sheets/Box
6	R1526	Ceramic Extreme+ Abrasive Sheets P400	P400	70mmx198mm	11m	55 Sheets/Box

## 3. TECHNICAL SPECIFICATIONS

No	Description	Units
1	Material	Ceramic with Aluminum Oxide
2	Size	70mm x 198mm
3	Colour	Orange
4	Hole configuration	Multi-holes
5	Package	55 Sheets/Box

## 4. PRODUCT CONSTRUCTION

No	Name	CAS#	Percentage
1	Ceramic and Aluminum Oxide	1344-28-1	80%
2	Inorganic Fluoride	60304-36-1	5%
3	Epoxy resin	25085-99-8	5%
4	Silicon Carbide	409-21-2	5%
5	Fiberglass Mesh	65997-17-3	5%

## 5. DIRECTIONS FOR USE

- Ideal for a range of jobs including paint removal and blocking of panels with fillers
- Used for metal, plastic, composite, wood, gel coats, and clearcoats
- Works best with RHINOMOTIVE sanding blocks R1116, R1115

## 6. SHELF LIFE

Not Applicable

## 7. PERFORMANCE PROPERTIES

Not Applicable

## 8. STORAGE

Store in a dry and well-ventilated area with 23°C and 50% relative humidity

## 9. TEST REPORT

Not Applicable

## 10. DISCLAIMER

Important Notice Purchaser: RHINOMOTIVE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The user is responsible for determining whether the RHINOMOTIVE product is fit for a particular purpose and suitable for user's application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform among the many factors that can affect the use and performance of a RHINOMOTIVE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the RHINOMOTIVE Automotive product to determine whether it is for a particular purpose and suitable for user's methods of application.

Limitation of Remedies and Liability: if the RHINOMOTIVE product is proved to be defective. THE EXCLUSIVE REMEDY, AT RHINOMOTIVE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE RHINOMOTIVE PRODUCT. RHINOMOTIVE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

**PRO  
SERIES** | **USE IT AND SEE  
THE DIFFERENCE**



RHINOMOTIVE LTD - UK  
71-75 Shelton Street, London, United Kingdom  
WWW.RHINOMOTIVE.COM