

CUSHION MAX

INTERFACE PAD 10MM X 150MM

PN: R1530

1. PRODUCT IDENTIFIER

Cushion Max Interface Pad 10mm X 150mm

1.1 Relevant uses: Used between disc and backup pad of the sanding machine to reduce friction and pressure

1.2 Details of the supplier of the safety data sheet

Company: RHINOMOTIVE LTD - UK 71-75 SHELTON STREET, LONDON, UNITED KINGDOM

Emergency Contact Number: +971 4 329 7775

Email: info@rhinomotive.com

2. AVAILABLE SIZES

No	P.N.	Product Name	Size
1	R1529	Cushion Max Interface Pad 5mm x 150mm	5mm x 150mm
2	R1530	Cushion Max Interface Pad 10mm x 150mm	10mm x 150mm

3. TECHNICAL SPECIFICATIONS

No	Description	Units
1	Thickness	5mm
2	Size Diameter	150mm
3	Colour	Black & White
4	Hole configuration	Multi-holes
5	Attachment type	Velcro

4. PRODUCT CONSTRUCTION

No	Name	CAS#	Percentage
1	Polyester foam type	113669-95-7	80%
2	Polyamide facing grip	63428-84-2	10%
3	Resin Polyamide	63428-84-2	10%

5. DIRECTIONS FOR USE

- Adds cushioning to back-up pads for consistent contact on uneven surfaces.
- Allows sanding around edges, delicate surfaces, contours, profiles
- Improves sanding result.

6. SHELF LIFE

Not Applicable

7. PERFORMANCE PROPERTIES

Not Applicable

8. STORAGE

Store in a dry and well-ventilated area from 0~40 °C and 30-60% relative humidity

9. TEST REPORT

No	Test Parameters	Result	Test Method
1	Oil content, % by mass	Absent	AOAC 920.85
2	Silicon Migration Test (with Filtration)	Nil	In house

9.1. Product Selection

Material: High Quality Wood Pulp Paper

Paper: No burr, No damage, No grease

Printing: The printing position must be uniform and clear

Filter: There is no excess glue in other parts of the product

9.2. Bond test

Test object: Paper filter

Test method: Tear off the filter from paper to see whether the bond is good, or pour 2L water

Test standard: The filters are not separated from the Paper

Test frequency: Every batch

10. DISCLAIMER

Important Notice Purchaser: RHINOMOTIVE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The user is responsible for determining whether the RHINOMOTIVE product is fit for a particular purpose and suitable for user's application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform among the many factors that can affect the use and performance of a RHINOMOTIVE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the RHINOMOTIVE Automotive product to determine whether it is for a particular purpose and suitable for user's methods of application.

Limitation of Remedies and Liability: if the RHINOMOTIVE product is proved to be defective. THE EXCLUSIVE REMEDY, AT RHINOMOTIVE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE RHINOMOTIVE PRODUCT. RHINOMOTIVE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.