



# CAR SHAMPOO

## WITH WAX 500 ML (CONCENTRATE)

**PN: R2208**

### 1. PRODUCT IDENTIFIER

Car Shampoo with Wax 500 ml (Concentrate)

1.1 Relevant uses: for car detailing professionals, easily removes contaminants and provides short term protection

1.2 Details of the supplier of the safety data sheet

Company: RHINOMOTIVE LTD - UK 71-75 SHELTON STREET, LONDON, UNITED KINGDOM

Emergency Contact Number: +971 4 329 7775

Email: info@rhinomotive.com

### 2. AVAILABLE SIZES

No	PN	Product Name	Volume
1	R1832	Car Shampoo with Wax19L	19 Liters
2	R2208	Car Shampoo with Wax500 ml	500 ml

### 3. TECHNICAL SPECIFICATIONS

No	Description	Units
1	Physical State	Liquid
2	Colour	Purple
3	Scent	Cherry
4	Water Soluble	Yes
5	Volume	500 ml
6	Ph	2:01

### 4. PRODUCT CONSTRUCTION

No	Chemical Name	CAS NUMBER	Percentage
1	Alkyl benzenesulfonic acid	68584-22-5	3 to 6%
2	Sodium Hydroxide	1310-73-2	< 2%
3	Sodium Chloride	7647-14-5	< 2%
4	Sodium Laureth Sulfate	68585-34-2	5-10%
5	Glycerin	56-81-5	< 1%
6	Water	7732185	80 to 86%



# CAR SHAMPOO

## WITH WAX 500 ML (CONCENTRATE)

**PN: R2208**

TECHNICAL DATA SHEET

### 5. DIRECTIONS FOR USE

- Dilute shampoo as per the mixing ratio
- Shake well before use
- Rinse the car thoroughly to remove any grit that could scratch the paint surface
- Wash vehicle using RHINOMOTIVE Car Wash Glove R1809 or RHINOMOTIVE Car Wash Sponge R1807
- Rinse thoroughly
- Dry with RHINOMOTIVE Magic Absorbent Towel R1802

#### 5.1. MIXING RATIO

- 1:80 (1 part concentrate and 80 parts water) Foam Gun Application
- 1:50 (1 part concentrate and 50 parts water) Manual wash

### 6. SHELF LIFE

Not Applicable

### 7. PERFORMANCE PROPERTIES

Not Applicable

### 8. STORAGE

- Store in a dry and well-ventilated area at 20 - 30°C and 30 - 60% relative humidity

### 9. TEST REPORT

Not Applicable

### 10. DISCLAIMER

Important Notice Purchaser: RHINOMOTIVE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The user is responsible for determining whether the RHINOMOTIVE product is fit for a particular purpose and suitable for user's application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform among the many factors that can affect the use and performance of a RHINOMOTIVE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the RHINOMOTIVE Automotive product to determine whether it is for a particular purpose and suitable for user's methods of application.

Limitation of Remedies and Liability: if the RHINOMOTIVE product is proved to be defective. THE EXCLUSIVE REMEDY, AT RHINOMOTIVE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE RHINOMOTIVE PRODUCT. RHINOMOTIVE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

**PRO  
SERIES**

**USE IT AND SEE  
THE DIFFERENCE**



RHINOMOTIVE LTD - UK  
71-75 Shelton Street, London, United Kingdom  
WWW.RHINOMOTIVE.COM