

1. PRODUCT IDENTIFIER

SUPER CEMENT REMOVER 500 ML (READY TO USE)

1.1 Relevant uses: For removing cement stains and acid rain spots

1.2. Details of the supplier of the safety data sheet

 ${\bf Company: RHINOMOTIVE\ LTD\ -\ UK\ 71\text{-}75\ SHELTON\ STREET,\ LONDON,\ UNITED\ KINGDOM\ }$

Emergency contact number +971 4 329 7775

Email: info@rhinomotive.com

2. AVAILABLE SIZES

| No | PN | Product Name | Volume |
|----|-------|--|--------|
| 1 | R1861 | Super Cement Remover 20L (Concentrate) | 19L |
| 2 | R2211 | Super Cement Remover 500 ml (Ready to Use) | 500 ml |

3. TECHNICAL SPECIFICATIONS

| No | Description | Units |
|----|----------------|-------------|
| 1 | Physical State | Liquid |
| 2 | Colour | Transparent |
| 3 | Scent | Pungent |
| 4 | Water Soluble | Yes |
| 5 | Volume | 500 ml |

4. PRODUCT CONSTRUCTION

| No | Chemical Name | CAS | Percentage % |
|----|--|-----------|--------------|
| 1 | Hydrochloric Acid (HCL) Dispersed in Water | 7647-01-0 | 12% - 14% |

5. DIRECTIONS FOR USE

- Shake well before use
- Apply a layer of diluted cement remover adequately onto the surface
- Leave for 15-20 minutes
- Wash with high pressure water
- Safe to use on aluminum, plastic, rubber, glass, and painted surfaces

www.rhinomotive.com



SUPER CEMENT REMOVER 500 ML (READY TO USE)

PN: R2211

6. SHELF LIFE

• One year from date of receipt by the customer when stored at 20 - 30°C and 30 - 60% relative humidity

7. PERFORMANCE PROPERTIES

Not applicable

8. STORAGE

Store in a dry and well-ventilated area between 20 - 30°C and 30 - 60% relative humidity

9. TEST REPORT

Not applicable

10. DISCLAIMER

Important Notice Purchaser: RHINOMOTIVE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The user is responsible for determining whether the RHINOMOTIVE product is fit for a particular purpose and suitable for user's application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform among the many factors that can affect the use and performance of a RHINOMOTIVE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the RHINOMOTIVE Automotive product to determine whether it is for a particular purpose and suitable for user's methods of application.

Limitation of Remedies and Liability: if the RHINOMOTIVE product is proved to be defective. THE EXCLUSIVE REMEDY, AT RHINOMOTIVE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE RHINOMOTIVE PRODUCT. RHINOMOTIVE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.











www. rhinomotive.com