



PAINT THICKNESS GAUGE

PN: R1154

1. PRODUCT IDENTIFIER

PAINT THICKNESS GAUGE

1.1 Relevant uses: Used to measure paint thickness

1.2 Details of the supplier of the safety data sheet

Company: RHINOMOTIVE LTD - UK 71-75 SHELTON STREET, LONDON, UNITED KINGDOM

Emergency Contact Number: +971 4 329 7775

Email: info@rhinomotive.com

2. AVAILABLE SIZES

Not Applicable

3. TECHNICAL SPECIFICATION

- Magnetic induction (F-probe) and eddy current (N-probe)
- Measuring range: 0 to 1300um
- 1-4-point calibration, zero calibration
- Adjustable alarm
- Minimum measuring diameter 6mm
- Minimum thickness: F-probe: 0.5mm, N-probe: 0.3mm
- Download data via USB interface Two 1.5v AAA battery
- Made in PRC

4. PRODUCT CONSTRUCTION

Name	CAS#	Percentage
Polyurethane	9009-54-5	100%

5. DIRECTIONS FOR USE

- Used to measure the thickness of the coated sheet on metal

6. SHELF LIFE

Not Applicable



PAINT THICKNESS GAUGE

PN: R1154

7. PERFORMANCE PROPERTIES

Refer to User Manual

8. STORAGE.

- Store in a dry and well-ventilated area between 0 - 30°C and 30 - 60% relative humidity

9. TEST REPORT

CE ROHS FCC ISO2178 ISO2360

10. DISCLAIMER

Important Notice Purchaser: RHINOMOTIVE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The user is responsible for determining whether the RHINOMOTIVE product is fit for a particular purpose and suitable for user's application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform among the many factors that can affect the use and performance of a RHINOMOTIVE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the RHINOMOTIVE Automotive product to determine whether it is for a particular purpose and suitable for user's methods of application.

Limitation of Remedies and Liability: if the RHINOMOTIVE product is proved to be defective. THE EXCLUSIVE REMEDY, AT RHINOMOTIVE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE RHINOMOTIVE PRODUCT. RHINOMOTIVE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

**PRO
SERIES**

**USE IT AND SEE
THE DIFFERENCE**



RHINOMOTIVE LTD - UK
71-75 Shelton Street, London, United Kingdom
WWW.RHINOMOTIVE.COM