

1. PRODUCT IDENTIFIER

PISTOL GRIP SANDER

1.1 Relevant uses: For sanding and surface preparation using roloc discs

1.2 Details of the supplier of the safety data sheet

Company: RHINOMOTIVE LTD - UK 71-75 SHELTON STREET, LONDON, UNITED KINGDOM

Emergency Contact Number: +971 4 329 7775

Email: info@rhinomotive.com

2. AVAILABLE SIZES

Not Applicable

3. TECHNICAL SPECIFICATION

No	Description	Units
1	FREE SPEED	17,000 r/min
2	Sanding Pad	3" (76 mm)
3	Spindle Thread	1/4"-20T
4	Air Consumption	12 CFM (340 L/min)
5	Overall Length	5-2/3" (145 mm)
6	Air Inlet	1/4" (6.35 mm)
7	Air Hose	3/8" (10 mm)
8	Air Pressure	90 psi (6.3 bar)
9	Net Weight	1.5 lbs (0.7 kg)

4. PRODUCT CONSTRUCTION

No	Name	CAS#	Percentage
1	Carbon Steel	7440-44-0	60%
2	Injection Molded Plastic	9002-88-4	40%

5. DIRECTIONS FOR USE

- Designed specifically for grinding and surface preparation
- Use with 2" and 3" RHINOMOTIVE Roloc Disc

www.rhinomotive.com 1/2



PISTOL GRIP SANDER

PN: R1118

6. SHELF LIFE

Not Applicable

7. PERFORMANCE PROPERTIES

Not Applicable

8. STORAGE.

Store in cool, or dry location.

9. TEST REPORT

Vibration EN ISO 28927-3	Noise EN ISO 15744	Remark
No-Load: 2.8 m/s² Uncertainty K= 1.5 m/s²	Sound Pressure Level No load: 77 dB(A)	Please always wear ear protector at environment noise level > 80 dB(A) due to risk of impaired hearing!
	Sound power level No load: 88 dB(A)	
	Uncertainty K= 3dB	

10. DISCLAIMER

Important Notice Purchaser: RHINOMOTIVE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The user is responsible for determining whether the RHINOMOTIVE product is fit for a particular purpose and suitable for user's application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform among the many factors that can affect the use and performance of a RHINOMOTIVE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the RHINOMOTIVE Automotive product to determine whether it is for a particular purpose and suitable for user's methods of application.

Limitation of Remedies and Liability: if the RHINOMOTIVE product is proved to be defective. THE EXCLUSIVE REMEDY, AT RHINOMOTIVE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE RHINOMOTIVE PRODUCT. RHINOMOTIVE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.











