



WATERPROOF SHEETS

280MM X 230MM, P80

PN: R1555

1. PRODUCT IDENTIFIER

WATERPROOF SHEETS 280MM X 230MM, P80

1.1. Relevant uses: Used for wet or dry sanding on Conventional and water base paints, primer, clear coats

1.2. Details of the supplier of the safety data sheet

Company: RHINOMOTIVE LTD - UK 71-75 SHELTON STREET, LONDON, UNITED KINGDOM

Emergency contact number +971 4 329 7775

Email: info@rhinomotive.com

2. AVAILABLE SIZES

No	PN	GRIT	SIZE	QUANTITY
1	R1555	P80	280mm x 230mm	25 Sheets/Box
2	R1556	P120	280mm x 230mm	25 Sheets/Box
3	R1557	P180	280mm x 230mm	25 Sheets/Box
4	R1558	P240	280mm x 230mm	25 Sheets/Box
5	R1559	P320	280mm x 230mm	25 Sheets/Box
6	R1560	P400	280mm x 230mm	25 Sheets/Box
7	R1561	P500	280mm x 230mm	25 Sheets/Box
8	R1562	P600	280mm x 230mm	25 Sheets/Box
9	R1563	P800	280mm x 230mm	25 Sheets/Box
10	R1564	P1000	280mm x 230mm	25 Sheets/Box
11	R1565	P1200	280mm x 230mm	25 Sheets/Box
12	R1534	P1500	140mm x 230mm	50 Sheets/Box
13	R1535	P2000	140mm x 230mm	50 Sheets/Box

3. TECHNICAL SPECIFICATIONS

No	Description	Units
1	Material	Grain: Silicon carbide, Bonding: Resin Backing: Latex paper
2	Size	280mm x 230mm
3	Colour	Black
4	Sanding Method	Manual
5	Package	50 Sheets/Box (280mm)



WATERPROOF SHEETS

280MM X 230MM, P80

PN: R1555

4. PRODUCT CONSTRUCTION

No	Name	CAS#	Percentage
1	Silicon carbide	409-21-2	90%
2	Resin bond	9003-07-0	5%
3	Latex	9006-04-6.	5%

5. DIRECTIONS FOR USE

- Wet or dry sanding - use for wet sanding and dry sanding without switching sandpaper
- Blend primer and paint - 1000/1200/1500/2000 grit is perfect for removing dust nibs and paint runs in color base coat. It is also ideal for smoothing heavy paint texture in clear coat.
- Convenient sheet can be used wet or dry on paint, conventional and water base paints, primer, clear coats
- Ideal for step 3 of the oem body repair system - paint. This stage includes painting the area and blending and smoothing primer and paint.
- Surfaces that can be sanded using wet or dry sheets is, mild steel, aluminum, fiberglass and plastics
- All grid sizes available to ensure step by step system sanding is achieved

6. SHELF LIFE

One year from date of receipt by the customer when stored at 20 - 30°C and 30 - 60% relative humidity

7. PERFORMANCE PROPERTIES

Not applicable

8. STORAGE

- Store in a dry and well-ventilated area between 20 - 30°C and 30 - 60% relative humidity

9. TEST REPORT

Not applicable

10. DISCLAIMER

Important Notice Purchaser: RHINOMOTIVE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The user is responsible for determining whether the RHINOMOTIVE product is fit for a particular purpose and suitable for user's application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform among the many factors that can affect the use and performance of a RHINOMOTIVE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the RHINOMOTIVE Automotive product to determine whether it is for a particular purpose and suitable for user's methods of application.

Limitation of Remedies and Liability: if the RHINOMOTIVE product is proved to be defective. THE EXCLUSIVE REMEDY, AT RHINOMOTIVE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE RHINOMOTIVE PRODUCT. RHINOMOTIVE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

TECHNICAL DATA SHEET

**PRO
SERIES**

**USE IT AND SEE
THE DIFFERENCE**



RHINOMOTIVE LTD - UK
71-75 Shelton Street, London, United Kingdom
WWW.RHINOMOTIVE.COM