



# HOOK AND LOOP SANDING BLOCK 14.8CM

**PN: R1183**

## 1. PRODUCT IDENTIFIER

Hook And Loop Sanding Block 14.8cm

1.1 Relevant uses: For wet and dry sanding

1.2 Details of the supplier of the safety data sheet

Company: RHINOMOTIVE LTD - UK 71-75 SHELTON STREET, LONDON, UNITED KINGDOM

Emergency Contact Number: +971 4 329 7775

Email: [info@rhinomotive.com](mailto:info@rhinomotive.com)

## 2. AVAILABLE SIZES

Not Applicable

## 3. TECHNICAL SPECIFICATIONS

| No | Description | Units        |
|----|-------------|--------------|
| 1  | Material    | Polyurethane |
| 2  | Size        | 14.8cm x 6cm |
| 3  | Colour      | Yellow       |
| 4  | Weight      | 90g          |

## 4. PRODUCT CONSTRUCTION

| No | Name              | CAS#      | Percentage |
|----|-------------------|-----------|------------|
| 1  | Polyurethane (PU) | 9009-54-5 | 100%       |

## 5. DIRECTIONS FOR USE

- Use for wet and dry sanding (P80 – P500 grits)
- Ideal for automotive, construction and woodworking industries



# HOOK AND LOOP SANDING BLOCK 14.8CM

**PN: R1183**

## 6. SHELF LIFE

Not Applicable

## 7. PERFORMANCE PROPERTIES

Not Applicable

## 8. STORAGE

- Store in a dry and well-ventilated area between 20 - 30°C and 30 - 60% relative humidity

## 9. TEST REPORT

Not Applicable

## 10. DISCLAIMER

Important Notice Purchaser: RHINOMOTIVE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The user is responsible for determining whether the RHINOMOTIVE product is fit for a particular purpose and suitable for user's application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform among the many factors that can affect the use and performance of a RHINOMOTIVE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the RHINOMOTIVE Automotive product to determine whether it is for a particular purpose and suitable for user's methods of application.

Limitation of Remedies and Liability: if the RHINOMOTIVE product is proved to be defective. THE EXCLUSIVE REMEDY, AT RHINOMOTIVE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE RHINOMOTIVE PRODUCT. RHINOMOTIVE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

TECHNICAL DATA SHEET

**PRO  
SERIES**

**USE IT AND SEE  
THE DIFFERENCE**



RHINOMOTIVE LTD - UK  
71-75 Shelton Street, London, United Kingdom  
WWW.RHINOMOTIVE.COM