



# ENGINE OIL FLUSH 3L

**PN: R1230**

## 1. PRODUCT IDENTIFIER

### ENGINE OIL FLUSH 3L

1.1. Relevant uses: Flushing agent for petrol and diesel engines .

1.2. Details of the supplier of the safety data sheet

Company: RHINOMOTIVE LTD - UK 71-75 SHELTON STREET, LONDON, UNITED KINGDOM

Emergency contact number +971 4 329 7775

Email: info@rhinomotive.com

## 2. AVAILABLE SIZES

No.	PN.	Product Name	Volume	Package
1	R1230	Engine Oil Flush 3l	3L	1Pc
2	R1231	Engine Oil Flush 5l	5L	1Pc

## 3. TECHNICAL SPECIFICATIONS

- Physical State: Liquid
- Color: Light Yellow
- Scent: Odourless
- Volume: 3 Litres
- Made in Germany

## 4. PRODUCT CONSTRUCTION

CAS No	Chemical name			Percentage
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics			10 - < 25%
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			

85535-85-9	Chlorparaffines C14-C28	1 - < 5%
	287-477-0	01-2119519269-33
	Lact., Aquatic Acute 1, Aquatic Chronic 1; H362 H400 H410 EUH066	
Varies - See Key to Abbreviations 93819-94-4	Base oil - highly refined	≥70 - 90%
	Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	≤3

## 5. DIRECTIONS FOR USE

- Run the engine until it reaches normal running temperature
- Drain the old oil.
- Refill the complete engine flush system using RHINOMOTIVE Engine Oil Flush R1230 to at least the minimum level. Do not overfill.
- Run the engine at idle for 5 to 10 minutes.
- Drain the flush oil. For heavy contamination, this step may be repeated.
- Finally, add new engine oil as per the manufacturer's specifications.

## 6. SHELF LIFE

24 months

## 7. PERFORMANCE PROPERTIES

Not applicable

## 8. STORAGE

- Store in a dry and well-ventilated area between 20 - 30°C and 30 - 60% relative humidity

## 9. TEST REPORT

Not applicable

## 10. DISCLAIMER

Important Notice Purchaser: RHINOMOTIVE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The user is responsible for determining whether the RHINOMOTIVE product is fit for a particular purpose and suitable for user's application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform among the many factors that can affect the use and performance of a RHINOMOTIVE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the RHINOMOTIVE Automotive product to determine whether it is for a particular purpose and suitable for user's methods of application.

Limitation of Remedies and Liability: if the RHINOMOTIVE product is proved to be defective. THE EXCLUSIVE REMEDY, AT RHINOMOTIVE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE RHINOMOTIVE PRODUCT. RHINOMOTIVE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.