

METAL INLAY CABLE TIES – BLACK, 100MM X 3MM

PN: R2109

1. PRODUCT IDENTIFIER

Metal Inlay Cable Ties – Black, 100mm x 3mm

1.1 Relevant uses: Used for tying cables, electrics, and general components in automotive, industrial, decorative, marine industries, etc.

1.2 Details of the supplier of the safety data sheet
 Company: RHINOMOTIVE LTD - UK 71-75 SHELTON STREET, LONDON, UNITED KINGDOM
 Emergency Contact Number: +971 4 329 7775
 Email: info@rhinomotive.com

2. AVAILABLE SIZES

No	PN	Tensile Strength	Size	Bundle Diameter	Color	Quantity
1	R2109	8kgs	100mm x 3mm	25mm	Black	200PCS
2	R2111	22kgs	300mm x 5mm	80mm	White	100PCS
3	R2112	50kgs	300mm x 8mm	80mm	Black	100PCS
4	R2113	50kgs	300mm x 8mm	80mm	White	100PCS

3. TECHNICAL SPECIFICATIONS

No	Description	Units
1	Material	UL approved Nylon 66 & Stainless steel 304
2	Colour	Black
3	Operating Temperature	-35°C to 85°C
4	Flammability	94V-2
5	Tensile Strength	8kgs
6	Bundle Diameter	25mm
7	Sizes	100mm x 3mm

4. PRODUCT CONSTRUCTION

No	Name	CAS#	Percentage
1	Nylon	25038-54-4	95%
2	Stainless steel	65997-19-5	5%



METAL INLAY CABLE TIES – BLACK, 100MM X 3MM

PN: R2109

5. DIRECTIONS FOR USE

- Widely used for tying cables, electrics, and general components in automotive, industrial, decorative, marine industries, etc.
- Used for all light and heavy applications

6. SHELF LIFE

24 Months

7. PERFORMANCE PROPERTIES

Not Applicable

8. STORAGE

- Store in a dry and well-ventilated area at 20 - 30°C and 30 - 60% relative humidity

9. TEST REPORT

Not Applicable

10. DISCLAIMER

Important Notice Purchaser: RHINOMOTIVE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The user is responsible for determining whether the RHINOMOTIVE product is fit for a particular purpose and suitable for user's application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform among the many factors that can affect the use and performance of a RHINOMOTIVE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the RHINOMOTIVE Automotive product to determine whether it is for a particular purpose and suitable for user's methods of application.

Limitation of Remedies and Liability: if the RHINOMOTIVE product is proved to be defective. THE EXCLUSIVE REMEDY, AT RHINOMOTIVE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE RHINOMOTIVE PRODUCT. RHINOMOTIVE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

TECHNICAL DATA SHEET

PRO
SERIES | **USE IT AND SEE**
THE DIFFERENCE



RHINOMOTIVE LTD - UK
71-75 Shelton Street, London, United Kingdom
WWW.RHINOMOTIVE.COM