

## 1. PRODUCT IDENTIFIER

#### TYRE TOOLS TROLLEY

1.1 Relevant use: Used in automotive workshop, for sheet metal work, assembling & disassembling and tyre repair tasks

1.2 Details of the supplier of the safety data sheet

Company: RHINOMOTIVE LTD - UK 71-75 SHELTON STREET, LONDON, UNITED KINGDOM Emergency Contact Number: +971 4 329 7775

Email: info@rhinomotive.com

## 2. AVAILABLE SIZES

No	PN	Product name	Package
1	R1179	Tools Trolley	1 PC
2	R3122	Comprehensive Pliers Tools - 12 Pcs	1 SET
3	R3123	Sheet Metal Tools – 14 Pcs	1 SET
4	R3124	Welding Clamp & Pliers Tools – 13 Pcs	1 SET
5	R3127	File & Chisel Tools - 44 Pcs	1 SET
6	R3134	Automotive Body Repair Tools -7 Pcs	1 SET

## 3. TECHNICAL SPECIFICATION

No	Body Material	Steel		
1	Duty Rating	Heavy Duty		
2	Number of Drawers	7		
3	Width x Depth x Height	88cm x 82cm x 52cm		
4	Drawer Storage Capacity	5 drawers – 20 kg, 2 drawers – 25kg		
5	Drawer Slides Ball Bearing, Full Extension			
6	Drawer Heights	rawer Heights 5 drawers 75mm, 2 drawers 154mm		
7	Load Capacity 150 kg			
8	Caster Size	5 in x 2 in		
9	Caster Type	(2) Fixed with Lock, (2) Swivel		
10	Locking System Keys			
11	Handles Easy Grip Steel			
12	Assembly Required No			
13	Finish Powder Coated			
14	Product Weight 54 Kg			

www.rhinomotive.com 1/2



# TYRE TOOLS

PN: R3119

#### 4. PRODUCT CONSTRUCTION

No	Name	CAS#	Percentage
1	Polyurethane	9009-54-5	25%
2	Chromium Vanadium Steel	89559-65-9	25%
3	Carbon Steel	7440-44-0	25%
4	Steel	7439-89-6	25%

#### 5. DIRECTIONS FOR USE

- Used in automotive workshop
- Designed to ensure toughness and structural integrity, this tools trolley has a steel construction, great for the workshop or garage
- It is built with seven drawers that is customized with 5 tool sets that covers all your tyre repair needs; all the tools are effectively organized in foam inlets
- Holding capacity of 150kg, providing plenty of storage for all your hardware. This high-quality tool trolley
  features a keyed lock to offer you peace of mind. It utilizes swivel and lockable casters and has an easy-grip
  steel handle for easily moving the unit

#### 6. SHELF LIFE

Not Applicable

## 7. PERFORMANCE PROPERTIES

Not Applicable

## 8. STORAGE

• Store in a dry and well-ventilated area between 20 - 30°C and 30 - 60% relative humidity

#### 9. TEST REPORT

Not Applicable

#### 10. DISCLAIMER

Important Notice Purchaser: RHINOMOTIVE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The user is responsible for determining whether the RHINOMOTIVE product is fit for a particular purpose and suitable for user's application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform among the many factors that can affect the use and performance of a RHINOMOTIVE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the RHINOMOTIVE Automotive product to determine whether it is for a particular purpose and suitable for user's methods of application.

Limitation of Remedies and Liability: if the RHINOMOTIVE product is proved to be defective. THE EXCLUSIVE REMEDY, AT RHINOMOTIVE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE RHINOMOTIVE PRODUCT. RHINOMOTIVE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.



USE IT AND SEE THE DIFFERENCE









